

DATA INTERFACE SUPPRESSION INDICATOR (DISI) CODES



Sally Pritsch
NAVSEA 04L55

WHAT ARE DISI CODES?

■ SCLSI TECH SPEC 9090-700C

- *The DISI controls the flow of ASI configuration, logistics and alteration data to SNAP and E52 Triggers to the ASI Allowance Computation Process.*
 - *“N” is used when config and supply parts/allowance information should not be carried in SNAP*
 - *“B” is used when config and supply parts/allowance information should be carried in SNAP*
 - *“A” is used when only config and supply parts info should be carried in SNAP; allowance information should not be carried in SNAP*

AIT MESSAGE 010728Z JUL 99



■ *WE KNOW YOU HAVE PROBLEMS WITH IT!*

- CDM set DISI Code to “A” for all planned installations

□ Why?

- Reduce churn

□ Issues

- Parts to ship
- Funding
- Difficulty in backing out of ships data base

WHERE DO WE GO FROM HERE?

YOU DECIDE



□ Options

- Setting the DISI Code to “A”
 - Establish timeframe to change DISI to “B”
- Modify DISI “A” to include APL and COSAL
- AIT bring parts on-board or Push/Pull provide
- Modify FMP Timelines
- Other suggestions
- Brief recommendation at CDM/ISEA Conf
- Modify AIT Message